



## SBR-A 高精度铝轴 Precision Steel Shafts



### 产品特性 Product Features

- 轴材料 EN AW 6061/6060
- 硬度 Hardness: 75 HB
- 表面 Surface: 硬质阳极氧化 Hard anodizing
- 表面硬度 Surface hardness: 450-550 HV
- 直线度 Straightness: EN 754-3
- 特殊轴可根据要求定制，请联系我们

Special shafts can be manufactured according to your requirement.  
Please contact with us.

### 标准规格 Standard Size Sheet

订购编码 Order P/N	直径 mm <sup>2</sup>	公差 Tolerance g6	标准长度 Standard Length ( mm )													绝缘厚度 Insulation thickness mm <sup>2</sup>	重量 Weight kg/m			
			200	300	400	500	600	700	800	900	1000	1200	1500	1800	2000			2500	3000	
SBR-R-06	6	h8	●	●	●	●													-	0.08
SBR-R-08	8	h8	●	●	●	●													-	0.14
SBR-R-10	10	h8	●	●	●	●	●												-	0.22
SBR-R-12	12	h8	●	●	●	●	●												-	0.32
SBR-R-16	16	h8	●	●	●	●	●	●	●	●	●	●	●						-	0.56
SBR-R-20	20	h8	●	●	●	●	●	●	●	●	●	●	●						-	0.88
SBR-R-20	20	h9	●	●	●	●	●	●	●	●	●	●	●						2	0.32
SBR-R-25	25	h8	●	●	●	●	●	●	●	●	●	●	●						-	1.37
SBR-R-25	25	h9	●	●	●	●	●	●	●	●	●	●	●						3	0.59
SBR-R-30	30	h8	●	●	●	●	●	●	●	●	●	●	●	●	●				7.5	1.48
SBR-R-40	40	h8	●	●	●	●	●	●	●	●	●	●	●	●	●				10	2.63
SBR-R-50	50	h8	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●		11	3.75

订购编码 Order P/N: SBR-A-06-1000

